



Product Specifications*

Type	Nd:YAG		
Wavelength	1064 nm		
Energy Per Pulse	40 Joules		
Fluence	5 to 900 J/cm ²		
Pulse Duration	20 to 100 Milliseconds		
Pulse Rate	up to 10 Hz		
Delivery Devices	VersaStat i™ Handpiece VersaStat i™ 10mm		
Spot Sizes	VersaStat i: 1 to 5 mm, continuously adjustable in 0.1 mm increments VersaStat i 10mm: 10 mm spot		
Aim Beam	<5 mW @ 635 ± 10 nm, adjustable		
Electrical Power-Laser (requires dedicated circuit)	208 VAC / 20 Amps, 60 Hz for U.S. 230 VAC / 20 Amps, 50 or 60 Hz outside the U.S.		
Electrical Power-Cart/Chiller	115 VAC / 15 Amps, 60 Hz for U.S. 230 VAC/10 Amps, 50 or 60 Hz outside the U.S.		
Cooling System-Laser	Internal, water-to-air cooled		
Cooling System-Cart/Chiller	37-48° F / 3-9° C internal temp in 72° F / 22° C room		
Weight	Laser only	With Cart/Chiller	
	73 lbs / 33 kgs	138 lbs / 62.5 kgs	
	Dimensions	Length 23 in / 59 cm	30 in / 77 cm
	Width 12 in / 31 cm	16 in / 41 cm	
	Height 17 in / 44 cm	38 in / 97 cm	
Warranty	One year parts and labor from date of installation or shipment. Other service options available upon request.		
CDRH Classification (U.S.)	Class IV		
IEC Equipment Classification (Europe and Canada)	Class 1		
IEC Laser Classification (Europe and Canada)	Class 4		

* Specifications are subject to change